



## Features

### Newland's best screen technology.

The 4" HD screen has a high transparency and low reflectivity to give crystal clear images, even in sunlight. The touchscreen responds when wearing gloves and maintains sensitivity even when wet. For added protection, Gorilla Glass 3 makes the N7 Cachalot Pro tougher and more damage resistant, making the device the perfect companion in rough environments.

### Android Enterprise Recommended (AER).

The N7 Cachalot Pro carries Google's AER seal of approval, signaling it keeps pace with performance and security upgrades to its operating system and core functionality. This label, in combination with Newland's free MDM Ndevor, enables clients to maintain secure visibility and control over their devices regardless of location.

### Fast charging, high-capacity and hot-swappable battery.

The N7 Cachalot Pro supports fast charging for its 5100mAh battery and is hot-swappable. This keeps your program running and your wifi connected, even when taking the battery fully out to exchange it with a new one.

### Near and far scanning, acuscan and multi-read mode

The N7 Cachalot Pro offers a choice of megapixel 2D scan engine. The

Standard-range version with acuscan provides standard, accurate scanning on codes close-up or smaller items. Alternatively, the Mid-range version is capable of reading codes on boxes and pallets from further away. Both scanners offer Newland's multi-read mode.

### Daisy chain charging.

The single cradle is designed to link to up to 3 additional cradles (4 in total), to limit the number of power outlets needed to charge units.

### The keys to unlock applications.

The N7 Cachalot Pro is designed to allow tailoring to many different applications for which a physical keyboard is still preferred. It offers the flexibility to choose between a 29, 38 and 47 keypad option (not including side scan buttons). Each of the three configurations are back-lit for high visibility in dark work environments.

### Seen and heard.

The applications most suited to the N7 Cachalot Pro are often in noisy environments. To accommodate for this, sound notifications can be adjusted to reach up to 90 decibels. When sound is not wanted, or instead, enough on its own, the device has vibration and a LED color feedback.



## Suggested industries



Industrial



Logistics



Warehousing

# N7 Cachalot Pro Technical specifications

## Performance

Operating System	Android 10 - GMS, Android Enterprise Recommended (AER)
Processor	Qualcomm Snapdragon 1.8GHz main frequency
Memory RAM	WiFi-only: 3GB. 4G: 4GB
Memory Flash	WiFi-only: 32GB. 4G: 64GB
Memory Storage Expansion (max.)	Micro SD/TF card (max. 128 GB)
Depth of Field EAN 13 (13mil)	SR: 40-480mm; MR: 130-705mm
Depth of Field CODE 39 (5mil)	SR: 80-350mm; MR: 200-575mm
Depth of Field PDF417 (6.67mil)	SR: 60-320mm; MR: 175-550mm
Depth of Field Data Matrix (10mil)	SR: 55-355mm; MR: 185-520mm
Depth of Field QR (15mil)	SR: 50-400mm; MR: 195-550mm

## Data Capture

1D	All major 1D symbologies, including Code 128, Code 49, Code 16K, (GS1128) UCC EAN-128, AIM-128, EAN-13, UPC-E, UPC-A, ITF, ITF 6, ITF 14, Matrix 2 of 5, Industrial 25, Standard 2 of 5, Code39, ISSN, ISBN, Codabar, Code93, Code 11, Plessey, MSI Plessey, RSS.
2D	All major 2D symbologies, including Aztec, Composite, CS Code, Maxicode, Micro PDF, Micro QR, PDF 417, QR Code, Data Matrix, DotCode.

## Physical

Dimensions (mm)	200(H) x 70(W) x 29(0) mm (pistol grip 58mm)
Weight	360g (including battery)
Display	4.0" WVGA IPS screen with Gorilla Glass, resolution 480x800, supports input with gloves
Keypad	29, 38 or 47 physical buttons, white backlight function
Buttons	Two scan buttons (left/right), three touch navigation keys
Interfaces	Quick charging (QC) 3.0, Type-C port, 9V/2A
Battery Type	3.8V, 5100 mAh, removable
Expected Battery Life	Scanning:> 15 hours of continuous operations; standby: 500 hours
Notifications	Vibrator, speaker, and multi-color LED
Power Supply Input	AC 100~240V, 50~60Hz
Power Supply Output	Type-C 9V/2A, 15V/1.2A
Sensors	Gravity Sensor, Hall Switch
Expansion Slot	MicroSD/TF card (max. 128GB)
Camera	13 Megapixels, PDAF, with LED flashlight
SIM	Nano+Nano or Nano+TF

## Environmental

Operating Temperature	-20°C to 55°C
Storage Temperature	-40°C to 70°C
Humidity	5% to 95% (non-condensing)
Electro Static Discharge (ESD)	±8 KV (direct discharge); ±15 KV (air discharge)

### Newland EMEA HQ

+31 (0) 345 87 00 33

[info@newland-id.com](mailto:info@newland-id.com)

[newland-id.com](http://newland-id.com)

Feel free to contact us or a partner near you

visit [newland-id.com/partners](http://newland-id.com/partners)

Specifications are subject to change without notice

© Newland EMEA 2021, all rights reserved

# N7 Cachalot Pro Technical specifications

Drop	1.8m
------	------

IP Rating	IP65
-----------	------

## Wireless

WWAN RADIO	2G: GSM: 850/900/1800/1900MHz; 3G: WCDMA: BI/B2/BS/B7/B8/ B20/B28a&b, CDMA Ix/EVDO: BCO; 4G: FDD-LTE: BI/B2/B3/BS/B7/B8/B20/B28a&b, TDD-LTE; B38/B39/B40/B41 (100M)
------------	---

WLAN RADIO	802.11 a/b/g/n/ac, compatible with 11 d/h/i/k/r/v/w, support 2.4G and 5G dual frequency; Roaming: Super Fast Roaming
------------	--

WPAN RADIO	Dual mode, Bluetooth 4.2+LE (backward compatible)
------------	---

RFID	NFC: 13.36MHz IS014443A/B, MI FARE, Felica, NFC Forum Tags
------	--

GPS	GPS-A, GPS-BeiDou, GLONASS
-----	----------------------------

## Accessories

Standard	Hand strap, USB cable, battery and multi-plug adapter (supports fast charging)
----------	--

Optional	Single cradle, pistol Grip, 4-slot battery charger, screen protection film
----------	--

## Software

MDM (certified)	Ndevor, SOTI, Airwatch
-----------------	------------------------

Terminal Emulation (compatible)	StayLinked, Ivanti Velocity
---------------------------------	-----------------------------

Configuration Tools	Ndevor
---------------------	--------

## Certifications

Hardware	CE-RED, FCC, BIS, RoHS2.0, REACH, AER, SOTI, UN38.3, IEC62471; Laser Safety: IEC60825
----------	---

## Warranty

Standard	2 years
----------	---------

### Newland EMEA HQ

+31 (0) 345 87 00 33

[info@newland-id.com](mailto:info@newland-id.com)

[newland-id.com](http://newland-id.com)

Feel free to contact us or a partner near you

visit [newland-id.com/partners](http://newland-id.com/partners)

Specifications are subject to change without notice

© Newland EMEA 2021, all rights reserved