



**HR42 Halibut  
Corded HD**  
Handheld Scanners

## Features

### Scan virtually any barcode.

Streamline and optimize your production line with the HR42 Halibut HD Corded. Using advanced technology, the device enhances the scanning of virtually every 1D and 2D barcode printed on paper, plastic and metal, as well as a range of direct part marks (DPMs).

### Unrivalled performance.

With its megapixel camera, the HR42 Halibut HD Corded raises the bar for handheld scanners. It is able to read small, dense barcodes and damaged barcodes faster and more accurately, ensuring maximum productivity no matter what.

### User-friendly aiming technology.

Designed with the end user in mind, the HR42 Halibut HD

Corded has a crisp and accurate laser aimer for point-and-shoot scanning.

### Rock-solid architecture.

Your employees can confidently use the Halibut HD Corded all day everyday due to its drop resistant housing (1.8m). Designed for light industrial environments, the Halibut gets the job done, even if they bump or drop it.

### Available with auto-sense stand for hands-free applications.

### Application scenarios.

Light-industrial applications, including electronic assembly, production line, healthcare, postal and financial.



## Suggested industries



# HR42 Halibut Coded HD Technical specifications

## Performance

Image Sensor	CMOS 1280×960
Processor	DDR3,800Mhz
Illumination	White LED
Aiming	650nm laser diode
Depth of Field EAN 13 (13mil)	25-155mm
Depth of Field CODE 39 (5mil)	50-100mm
Depth of Field PDF417 (6.67mil)	40-105mm
Depth of Field Data Matrix (10mil)	40-110mm
Depth of Field QR (15mil)	35-155mm
Minimal Print Contrast	25%
Scan Angle Roll	360°
Scan Angle Pitch	±50°
Scan Angle Skew	±50°
Field of View Horizontal	40.5°
Field of View Vertical	30.4°
Scan Modes	Level Mode, Sense Mode, Continuous Mode, Batch Mode
Scan Rate	60 frames per second
Motion Tolerance	2m/s

## Data Capture

1D	All major 1D symbologies, including EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128, Code93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, GS1 Databar, Code 39, Code 11, MSI-Plessey, Plessey.
2D	All major 2D symbologies, including PDF417, QR Code, Data Matrix, Aztec, Maxicode.

## Physical

Dimensions (mm)	115(L)×74(W)×161(H)mm
Weight	173g
Material	PC, ABS
Buttons	Trigger
Interfaces	RS-232, USB
Notifications	Beep, LED indicator
Input Voltage	5VDC±5%
Current @ 5VDC Operating	266mA (typical), 344mA (max.)
Current @ 5VDC Standby	109mA
Power Consumption	1251mW (typical)
Power Supply Input	DC5V, 1.5A
Power Supply Output	AC100~240V, 50~60Hz

### Newland EMEA HQ

+31 (0) 345 87 00 33

[info@newland-id.com](mailto:info@newland-id.com)

[newland-id.com](http://newland-id.com)

Feel free to contact us or a partner near you

visit [newland-id.com/partners](http://newland-id.com/partners)

Specifications are subject to change without notice

© Newland EMEA 2021, all rights reserved

# HR42 Halibut Corded HD Technical specifications

## Environmental

Operating Temperature	-20°C to 50°C (-4°F to 122°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Humidity	5%~95% (non-condensing)
Electro Static Discharge (ESD)	±8 KV (direct discharge); ±16 KV (air discharge)
Drop	1.8m
IP Rating	IP42

## Accessories

Standard	USB Cable, Adapter
Optional	Foldable Stand

## Software

Configuration Tools	Nset
---------------------	------

## Certifications

Hardware	FCC Part15 Class B, CE EMC Class B, IEC 60825-1, KC
----------	-----------------------------------------------------

## Warranty

Standard	5 years
----------	---------

### Newland EMEA HQ

+31 (0) 345 87 00 33

[info@newland-id.com](mailto:info@newland-id.com)

[newland-id.com](http://newland-id.com)

Feel free to contact us or a partner near you

visit [newland-id.com/partners](http://newland-id.com/partners)

Specifications are subject to change without notice

© Newland EMEA 2021, all rights reserved